

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 844 801 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.05.1998 Bulletin 1998/22

(51) Int. Cl.⁶: H04Q 7/38, H04B 7/02

(21) Application number: 97309551.6

(22) Date of filing: 25.11.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE

Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 25.11.1996 JP 313958/96

(71) Applicant: NEC CORPORATION
Tokyo (JP)


(72) Inventor: Suzuki, Hideto
Minato-ku, Tokyo (JP)

(74) Representative:
Moir, Michael Christopher et al
Mathys & Squire
100 Gray's Inn Road
London WC1X 8AL (GB)

(54) Cellsite station having switcher units to implement intra-cell handover

(57) In a cellular mobile communication system, a number of transmit/receive units are respectively connected to antenna sites for conversion of signals between a radio frequency and a baseband frequency and a number of modulator/demodulator units is provided. Control circuitry receives signals from the modulator/demodulator units indicating strengths of signals

received by the antennas and controls a switcher for establishing connections between the transmit/receive units and the modulator/demodulator units. Control circuit further controls a combining circuit to combine the signals associated with at least two of the modulator/demodulator units during an intra-cell handover.



systems are switched in the switcher 7 and diversity combined in the combining circuit 10 in the same way as those of the corresponding receive systems.

Due to the provision of the switcher 7 between the radio frequency side and the modulation/demodulation side of the base station, soft handover can be achieved without using complex circuitry and the number of leads which would otherwise be required between them can be reduced. Furthermore, by the use of A/D converters 3 and D/A converters 4 on one side of the switcher 7 and P/S converters 8 and S/P converters 9 on the other side, signals can be switched at high speeds and hence high-speed digital signal processing can be achieved by demodulators 9 and modulators 11. In addition, the use of P/S converters 8 and S/P converters 9 reduces the number of conductors leaving the modulators 11. This is advantageous for implementation of the modulator/demodulator circuitry.

Each feature disclosed in this specification (which term includes the claims) and/or shown in the drawings may be incorporated in the invention independently of other disclosed and/or illustrated features.

The text of the abstract filed herewith is repeated here as part of the specification.

In a cellular mobile communication system, a number of transmit/receive units are respectively connected to antenna sites for conversion of signals between a radio frequency and a baseband frequency and a number of modulator/demodulator units is provided. Control circuitry receives signals from the modulator/demodulator units indicating strengths of signals received by the antennas and controls a switcher for establishing connections between the transmit/receive units and the modulator/demodulator units. Control circuit further controls a combining circuit to combine the signals associated with at least two of the modulator/demodulator units during an intra-cell handover.

Claims

1. A cellular mobile communication system comprising:

a plurality of antennas (1);
a plurality of transmit/receive units (2) connected respectively to said antennas for conversion of signals between a radio frequency and a frequency lower than the radio frequency;
a plurality of modulator/demodulator units (9, 11);
control means (13) for receiving signals from said modulator/demodulator units indicating strengths of signals received by said antennas;
switch means (7) responsive to a first control signal from said control means for establishing connections between said transmit/receive units (2) and said modulator/demodulator units

(9, 11); and

combining means (10) responsive to a second control signal from said control means for combining signals associated with at least two of said modulator/demodulator units during a handover operation.

2. A cellular mobile communication system as claimed in claim 1, wherein said modulator/demodulator units (9, 11) comprise code division multiple access modulator/demodulator units.
3. A cellular mobile communication system as claimed in claim 1 or 2, wherein said modulator/demodulator units comprise digital modulator/demodulator units, further comprising:


a plurality of analog-to-digital converters (3) and a plurality of digital-to-analog converters (4) connected between said transmit/receive units (2) and said switch means (7), each of said analog-to-digital converters producing a multi-bit parallel output signal and each of said digital-to-analog converters receiving a multi-bit parallel input signal; and
a plurality of parallel-to-serial converters (8) and a plurality of serial-to-parallel converters (12) connected between said switch means (7) and said modulator/demodulator units (9, 11), each of the parallel-to-serial converters converting a said multi-bit parallel output signal to a serial output signal and supplying the serial output to a corresponding one of said modulator/demodulator units and each of the serial-to-parallel converters converting an output signal from a corresponding one of the modulator/demodulator units to a said multi-bit parallel input signal.


4. A cellular mobile communication system as claimed in claim 1 or 2, wherein said frequency lower than the radio frequency signal is a baseband frequency.
5. A cellular mobile communication system as claimed in claim 1 or 2, wherein said antennas cover a plurality of equally segmented areas of a cell-site base station.
6. A cellular mobile communication system as claimed in claim 1 or 2, wherein said antennas are located alongside of a street.
7. A cellular mobile communication system as claimed in claim 1 or 2, wherein said antennas are located in dead spot zones of a cell-site base station.
8. A cellular mobile communication system as claimed in claim 3, wherein connections between said paral-

l-to-serial converters and said serial-to-parallel converters and said modulator/demodulator units are formed by coaxial cables.

munication using the RF signal previously selected is discontinued, the demodulated signals from the two RF signals being diversity combined.

9. A cellular mobile communication system as claimed in claim 1 or 2, wherein said control means (13) is arranged to select a first group of mutually adjacent antennas and then select a second group of mutually adjacent antennas and control said switch means (7) according to the selected first and second groups. 5 10
10. A communication method for a cellular mobile communication system, wherein the system comprises a plurality of antennas (1), a plurality of transmit/receive units (2) connected respectively to said antennas for conversion of signals between a radio frequency and a frequency lower than the radio frequency, a plurality of modulator/demodulator units (9, 11); and switch means (7) disposed between said transmit/receive units and said modulator/demodulator units, the method comprising the steps of: 15 20
- a) controlling said switch means (7) to establish connections between said transmit/receive units (2) and said modulator/demodulator units (9, 11); 25
 - b) making comparisons between signals from said modulator/demodulator units (9, 11) indicating strengths of signals received by said antennas to determine relative strengths of said signals; 30
 - c) determining at least two of said modulator/demodulators according to the relative strengths of said signals during a handover operation; and 35
 - d) combining signals associated with said at least two modulator/demodulator units. 40
11. The method of claim 10, wherein the step (a) comprises the steps of selecting a first group of mutually adjacent antennas and then selecting a second group of mutually adjacent antennas and controlling said switch means (7) according to the selected first and second groups. 45
12. A soft intra-cell handover method in a cellular mobile communication system comprising receiving a radio-frequency signal via a plurality of receiving antennas, demodulating each received RF signal, comparing the strengths of the demodulated signals, and establishing radio communication by selecting the RF signal providing the strongest demodulated signal for the time being, characterised in that, when another RF signal provides a stronger demodulated signal, communication is established by selecting that RF signal before com- 50 55





THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 844 801 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
23.08.2000 Bulletin 2000/34

(51) Int. Cl.⁷: H04Q 7/38, H04B 7/02

(43) Date of publication A2:
27.05.1998 Bulletin 1998/22

(21) Application number: 97309551.6

(22) Date of filing: 25.11.1997

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Suzuki, Hideto
Minato-ku, Tokyo (JP)

(74) Representative:
Moir, Michael Christopher et al
Mathys & Squire
100 Gray's Inn Road
London WC1X 8AL (GB)

(30) Priority: 25.11.1996 JP 31395896

(71) Applicant: NEC CORPORATION
Tokyo (JP)

(54) Cellsite station having switcher units to implement intra-cell handover

(57) In a cellular mobile communication system, a number of transmit/receive units are respectively connected to antenna sites for conversion of signals between a radio frequency and a baseband frequency and a number of modulator/demodulator units is provided. Control circuitry receives signals from the modulator/demodulator units indicating strengths of signals

received by the antennas and controls a switcher for establishing connections between the transmit/receive units and the modulator/demodulator units. Control circuit further controls a combining circuit to combine the signals associated with at least two of the modulator/demodulator units during an intra-cell handover.




FIG. 1

EP 0 844 801 A3

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 30 9551

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X A	WO 92 17954 A (PACTEL CORP) 15 October 1992 (1992-10-15) * page 28, line 11 - page 29, line 18; figure 10 *	1,2,10, 12 3-9,11	H04Q7/38 H04B7/02
X	WO 91 07019 A (PACTEL CORP) 16 May 1991 (1991-05-16) * page 8, line 3 - page 12, line 11; figure 2 *	1,10,12	
A	WO 95 05722 A (MACNAMEE ROBERT JOSEPH GERARD) 23 February 1995 (1995-02-23) * page 5, line 6 - page 8, line 12; figures *	1,10,12	
A	WO 91 07043 A (PACTEL CORP) 16 May 1991 (1991-05-16) * page 8, line 25 - page 12, line 27 *	1,10,12	
A	US 5 119 501 A (PASSMORE RODERICK J ET AL) 2 June 1992 (1992-06-02) * column 3, line 39 - column 4, line 30; figures *	1,10,12	<div>TECHNICAL FIELDS SEARCHED (Int.Cl.6)</div> <div>H04Q H04B</div>
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 June 2000	Examiner Gastaldi, G
<div>CATEGORY OF CITED DOCUMENTS</div> <div> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document </div> <div> T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document </div>			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 30 9551

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-06-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9217954 A	15-10-1992	US 5243598 A	07-09-1993
		EP 0578741 A	19-01-1994
		JP 6506335 T	14-07-1994
		US 5504936 A	02-04-1996
		US 5479397 A	26-12-1995
		US 5678186 A	14-10-1997
		US 5983118 A	09-11-1999
WO 9107019 A	16-05-1991	CA 2106017 A	14-03-1995
		EP 0500654 A	02-09-1992
		JP 5503616 T	10-06-1993
		US 5193109 A	09-03-1993
WO 9505722 A	23-02-1995	AU 7272394 A	14-03-1995
		EP 0713631 A	29-05-1996
WO 9107043 A	16-05-1991	EP 0502019 A	09-09-1992
		JP 7079508 B	23-08-1995
		JP 4507177 T	10-12-1992
		US 5067147 A	19-11-1991
US 5119501 A	02-06-1992	CA 2034401 A	20-10-1991
		CA 2040061 A	20-10-1991
		DE 69126235 D	03-07-1997
		DE 69126235 T	08-01-1998
		DK 454368 T	30-06-1997
		EP 0454368 A	30-10-1991
		ES 2100932 T	01-07-1997
		HK 1007847 A	23-04-1999
		JP 2708137 B	04-02-1998
		JP 6006276 A	14-01-1994

THIS PAGE BLANK (USPTO)